

# 2009 **FOURTRAX FOREMAN FAMILY**



*With four great models in the Foreman lineup, you're sure to find one that's perfect for you.*

**FOURTRAX FOREMAN 4X4/ES/EPS** Whether you're riding deep into the back country to bag a trophy elk or patrolling an endless fence line, the FourTrax® Foreman® 4X4 is designed to make the toughest tasks a whole lot easier. Its tough-as-nails 475cc longitudinal Honda engine delivers tons of torque, week after week and year after year. And our TraxLok® selectable 2WD/4WD system lets you flip to 4WD on the fly. And to give you even more options you can choose a Foreman with our Electric Shift Program™ (ESP®) and another with EPS, our revolutionary Electric Power Steering. Why do we pay such attention to getting the job done? Three simple words: It's a Honda.



Red



Olive



Black



Natural Gear™ Camo

## UNIQUE FEATURES

- Powerful four-stroke 475cc OHV air-cooled longitudinally mounted engine allows direct driveshaft alignment to both front and rear wheels for improved drivetrain efficiency.
- The overhead-valve arrangement features angled valves in a hemispherical combustion chamber for straighter intake and exhaust flow, resulting in improved engine performance.
- Torque-sensitive front differential makes steering lighter in four-wheel drive.
- TraxLok® allows you to shift between 2WD and 4WD on the fly with just a push of your thumb.
- Maintenance-free shaft drive with torque-sensing front differential routes power directly from the longitudinally mounted engine without inefficient directional changes.
- Optional Electric Power Steering (EPS) makes riding through ruts or over boulder fields easier than ever.

## SPECIFICATIONS

Model	TRX500FPE (with EPS)/TRX500FPM/TRX500FE (with ESP)/TRX500FM	
<b>ENGINE</b>		
Engine	475cc air-cooled OHV longitudinally mounted single-cylinder four-stroke	
Compression Ratio	8.5:1	
Bore & Stroke	92mm x 71.5mm	
Induction	Keihin® 36mm constant-velocity (CV) carburetor	
Ignition	CD with electronic advance	
<b>CHASSIS / SUSPENSION / BRAKES</b>		
Front Suspension	Independent double-wishbone; 6.7-inch travel	
Rear Suspension	Swingarm with dual shocks; 6.7-inch travel	
Front Brake	Dual hydraulic 180mm disc	
Rear Brake	Sealed 180mm mechanical drum	
<b>DIMENSIONS</b>		
Wheelbase	50.7 inches	
Seat Height	33.9 inches	
Ground Clearance	7.5 inches	
Curb Weight*	639 lbs. (FPE)/637 lbs. (FPM) 624 lbs. (FE)/620 lbs. (FM)	
Fuel Capacity	4.1 gallons, including 0.7-gallon reserve	
<b>DRIVETRAIN</b>		
Transmission	Electric Shift Program five-speed with Reverse (FPE/FE)/Five-speed with Reverse (FPM/FM)	
<b>FACTORY WARRANTY</b>		
1 Year	Coverage of defects in materials and workmanship	

## ENVIRONMENTAL COMMITMENT

At Honda, we believe in performance and leadership, and that's why we're taking a leadership position when it comes to the environment. We continue to develop low-emission technologies for our current and future motorcycles, ATVs, scooters and personal watercraft. And that's the kind of performance everybody can appreciate.

UTILITY ATVs ONLY FOR RIDERS 16 & OLDER. ATVs CAN BE HAZARDOUS TO OPERATE. FOR YOUR SAFETY, BE RESPONSIBLE. READ YOUR OWNER'S MANUAL. ALWAYS WEAR HELMET, EYE PROTECTION & PROTECTIVE CLOTHING. BE CAREFUL ON DIFFICULT TERRAIN. ALL ATV RIDERS SHOULD TAKE A TRAINING COURSE (FREE FOR NEW BUYERS, ASK YOUR DEALER OR CALL ASI 800-887-2887). NEVER RIDE: UNDER THE INFLUENCE OF DRUGS OR ALCOHOL, ON PAVED SURFACES, PUBLIC ROADS, WITH PASSENGERS, AT EXCESSIVE SPEEDS. NO STUNT RIDING. RESPECT THE ENVIRONMENT WHEN RIDING. Whenever you ride off-road, follow the "Tread Lightly!" guidelines, and always stay on established trails in approved areas. Operating your ATV with a modified engine, exhaust system, spark arrestor or noise control system may be illegal. Natural Gear™ is a registered trademark of NATGEAR, LLC. Keihin is a registered trademark of Keihin Mfg. Co., Ltd. FourTrax®, Foreman®, TraxLok®, Electric Shift Program™ and ESP® are trademarks of Honda Motor Co., Ltd. ©2008 AHMC

